

# CORSA Gloss Tire Finish



PRODUCT NAME: CORSA Gloss Tire Finish  
 PRODUCT ID#: CCC-008  
 DATE PREPARED: 02.2010

## 1. Chemical Product And Company Identification

PRODUCT NAME: CORSA Gloss Tire Finish  
 PRODUCT DESCRIPTION: CCC-008  
 MANUFACTURER: Corsa Car Care  
 12318 Lower Azusa Road  
 Arcadia, CA 91006-5872

## 2. Composition/Information On Ingredients

HAZARDOUS COMPONENTS	OSHA PEL	ACGIH TLV	TWA	PERCENT
PETROLEUM DISTILLATES		75-80		

CAS # 68551-19-9

## 3. Hazard Identification

PRIMARY ROUTES OF ENTRY:  
 Dermal- Yes      Ingestion- Yes      Inhalation- Yes

POTENTIAL HEALTH HAZARD(Acute and Chronic):

EYES: Mild eye irritant. Direct contact with the solution may cause slight iridal and conjunctival irritation. No permanent damage is anticipated. SKIN: Can be mildly irritating upon prolonged exposure. May also defat skin. INGESTION: Can cause symptoms such as, but not limited to, gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard. INHALATION: Can cause symptoms such as, but not limited to, coughing, dizziness, nausea, fatigue, pulmonary disorders, or asphyxiation. May aggravate pre-existing lung disorders (i.e.asthma).

CARCINOGENICITY:  
 NTP- NO      IARC MONOGRAPH- NO      OSHA REGULATED- NO

## 4. First Aid Measures

EYES: Flush immediately with clean, free flowing water for 15 minutes. Consult a physician if irritation persists. SKIN: Wash thoroughly with soap and water. INGESTION: Give a quart or more of water to drink. DO NOT INDUCE VOMITING (aspiration hazard). Never administer liquids by mouth to unconscious persons. Provide medical attention. INHALATION: Remove person to fresh air. If not breathing, administer artificial respiration including oxygen. Provide medical attention.

## 5. Fire Fighting Measures

FLAMMABLE PROPERTIES	METHOD USED:
FLASH POINT: > 174 ° F	TCC
FLAMMABLE LIMITS	LEL: ND      UEL: ND

EXTINGUISHING MEDIA: Water, CO<sub>2</sub>, Dry Chemical, Foam.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus when fighting fires involving chemicals.

UNUSUAL FIRE AND EXPLOSION HAZARD: This material is combustible and may be ignited by extreme heat or flame. Vapors can travel considerable distances to a source of ignition where they can ignite.

## 6. Accidental Release Measures

Observe precautions from other sections. Collect any spills with absorbent material such as vermiculite. Place collected material in a polyethylene lined metal container and seal. Clean up residue with water.

NA=Not Applicable    N/A=Not Available      ND=Not Determined

## 7. Handling And Storage

Avoid contact with eyes. Avoid prolonged and repeated skin contact.

Avoid breathing vapors. Use with adequate ventilation. Store in a cool dark place. Keep away from heat, flames or sparks. See other precautions listed elsewhere within this MSDS.

## 8. Exposure Controls/Personal Protection

RESPIRATORY PROTECTION: None required if ventilation is adequate to keep below TLV.

LOCAL EXHAUST: Recommended to keep air contaminant concentration below the OSHA's PEL and ACGIH's TLV.

MECHANICAL EXHAUST: General ventilation system should be provided.

PROTECTIVE GLOVES: Neoprene rubber gloves.

EYE PROTECTION: Safety goggles.

OTHER PROTECTIVE EQUIPMENT: Eyewash equipment. Apron, coveralls, boots as necessary to prevent skin contact. Safety shower.

WORK/HYGIENIC PRACTICES: Wash hands thoroughly before handling

foodstuffs, liquids, or tobacco products.

OTHER HEALTH HAZARDS: If TLV of any component of the product is exceeded, a NIOSH/MSHA jointly approved respirator must be supplied to personnel and used in accordance with OSHA Regulations. Respiratory protection programs must be in accordance with 29CFR 1910.134

## 9. Physical And Chemical Properties

BOILING POINT:	(deg.F): 422.6 - 474.8 F
VAPOR PRESSURE:	(68 deg. F) < 1
VAPOR DENSITY:	(Air=1.0) > 3
SOLUBILITY IN WATER:	None
SPECIFIC GRAVITY:	(H <sub>2</sub> O=1) .78
VOLATILE BY VOLUME:	78%
VOC CONTENT:	(LVP solvent)
VOC EXEMPT COMPONENTS:	100%
EVAPORATION RATE:	(Ether=1) < 1
APPEARANCE:	Clear to transparent liquid
ODOR:	Solvent

NA=Not Applicable    N/A=Not Available      ND=Not Determined

## 10. Stability And Reactivity

STABILITY (CONDITIONS TO AVOID): Avoid open flames, sparks, hot glowing surfaces or electric arcs.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, bases, oxidizing agents and selected amines.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Thermal decomposition can produce CO<sub>2</sub>, CO.

HAZARDOUS POLYMERIZATION: Will not occur

## 11. Toxicological Information

No information available.

## 12. Ecological Information

No information available.

## 13. Disposal Considerations

Dispose in accordance with Federal, State, and Local Regulations (May be incinerated in accordance with FEDERAL, STATE AND LOCAL REGULATIONS).

## 14. Transport Information

PROPER SHIPPING NAME:	HYDROCARBONS, LIQUID N.O.S.UN
NUMBER:	UN 3295

COMBUSTIBLE LIQUID, III

## 15. Regulatory Information

CORSA Gloss Tire Finish has no ingredients subject to reporting requirements of SARA 313 and 40 CFR 372.

## 16. OTHER INFORMATION

### IMPORTANT NOTICE

The information presented in this publication is believed to be accurate. However, NO WARRANTY OF FITNESS OR MERCHANTABILITY or of any kind, either expressed or implied, is made regarding the product described herein or the information or recommendations contained herein. Since the conditions of use, handling and storage of this product are not within Corsa Car Care's control, Corsa Car Care assumes no liability or responsibility with respect to personal injury or property damage resulting there from or with respect to results obtained from use of CORSA Gloss Tire Finish.